

AF 60 2.5-2 ER11



TYPE	VOLTAGE [Volt]	FREQUENCY [Hz]	RPM	DELIVER POWER [Kw]	ABSOR. [Amp]	Cos j	WEIGHT [Kg]
AF60 2.5/2 compressed air	220	400	24000	0,20	1,4	0,70	2
2.5/2 liquid	220	400	24000	0,25	1,8	0,70	2
AF60 2.5/2 compressed air	380	400	24000	0,20	0,8	0,70	2
2.5/2 liquid	380	400	24000	0,25	1,0	0,70	2
AF60 2.5/2 compressed air	220	400/670	24000/40000	0,20	1,4	0,70	2
2.5/2 liquid	220	400/670	24000/40000	0,25	1,0	0,70	2
AF60 2.5/2 compressed air	380	400/670	24000/40000	0,20	0,8	0,70	2
2.5/2 liquid	380	400/670	24000/40000	0,25	1,0	0,70	2
AF60 6/2 compressed air	220	400	24000	0,35	1,9	0,70	2,5
6/2 liquid	220	400	24000	0,55	2,6	0,75	2,5
AF60 6/2 compressed air	380	400	24000	0,35	1,1	0,75	2,5
6/2 liquid	380	400	24000	0,55	1,5	0,75	2,5
AF60 6/2 compressed air	220	400/670	24000/40000	0,35	1,9	0,75	2,5
6/2 liquid	220	400/670	24000/40000	0,55	2,6	0,75	2,5
AF60 6/2 compressed air	380	400/670	24000/40000	0,35	1,1	0,75	2,5
6/2 liquid	380	400/670	24000/40000	0,50	1,5	0,75	2,5

